

## Attestation of Conformity

No. N8A 072092 0291 Rev. 00

**Holder of Certificate:** Shanghai JA Solar Technology Co., Ltd.

No. 118, Lane 3111,  
West Huancheng Road  
Fengxian District  
201401 Shanghai  
PEOPLE'S REPUBLIC OF CHINA

**Product:**

### Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

#### Poly-Crystalline Silicon Photovoltaic Module

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance.  
It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 704061604126-09

Date, 2018-12-04

( Zhulin Zhang )

giri

## Attestation of Conformity

**No. N8A 072092 0291 Rev. 00**

**Model(s):**

1500 V DC Maximum System voltage,  
Fire Safety Class C Modules:  
JAP6(K)-72-xxx/4BB/1500V, xxx= 310 to 330 in step of 5;  
JAP6(K)-60-xxx/4BB/1500V, xxx= 255 to 275 in step of 5;  
1500 V DC Maximum System voltage,  
Fire Safety Class A Modules:  
JAP72D00-xxx/SC, xxx= 310 to 330 in step of 5;  
JAP60D00-xxx/SC, xxx= 260 to 285 in step of 5;  
JAP72D00-xxx/PR, xxx= 330 to 345 in step of 5;  
JAP60D00-xxx/PR, xxx= 275 to 290 in step of 5;  
1000 V DC Maximum System voltage,  
Fire Safety Class C Modules:  
JAP6(K)-72-xxx/4BB, xxx= 310 to 330 in step of 5;  
JAP6(K)-60-xxx/4BB, xxx= 255 to 275 in step of 5;  
JAP72S02-xxx/SC, xxx= 310 to 335 in step of 5;  
JAP60S02-xxx/SC, xxx= 255 to 280 in step of 5;  
JAP72S02-xxx/PR, xxx= 330 to 345 in step of 5;  
JAP60S02-xxx/PR, xxx= 275 to 285 in step of 5;  
JAP72S08-xxx/SC, xxx =320 to 345, in step of 5;  
JAP60S08-xxx/SC, xxx =270 to 290, in step of 5;  
JAP72S08-xxx/PR, xxx =335 to 355, in step of 5;  
JAP60S08-xxx/PR, xxx =280 to 295, in step of 5;  
1000 V DC or 1500 V DC Maximum System voltage,  
Fire Safety Class C Modules:  
JAP72S01-xxx/SC, xxx= 310 to 335 in step of 5;  
JAP60S01-xxx/SC, xxx= 255 to 280 in step of 5;  
JAP72S01-xxx/PR, xxx= 330 to 345 in step of 5;  
JAP60S01-xxx/PR, xxx= 275 to 285 in step of 5;  
JAP72S03-xxx/SC, xxx =320 to 345, in step of 5;  
JAP60S03-xxx/SC, xxx =270 to 290, in step of 5;  
JAP72S03-xxx/PR, xxx =335 to 355, in step of 5;  
JAP60S03-xxx/PR, xxx =280 to 295, in step of 5;  
xxx is standing for rated output power at STC

### Parameters:

Construction:	Framed or Frameless, with Junction box, Cable and Connectors.
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute No. 10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P. R. China
Safety Class:	Class II
Maximum System Voltage:	1500 or 1000 V DC

**Tested  
according to:**

EN 61730-1:2018  
EN 61730-2:2018

gzi