

PS2-600 C-SJ3-9

Solar Submersible Pump System for 4" wells

System Overview

Head max. 50 m Flow rate max. 4,1 m³/h

Technical Data

Controller PS2-600

- Controlling and monitoring
- Control inputs for dry running protection, remote control etc.
- Protected against reverse polarity, overload and overtemperature
- Integrated MPPT (Maximum Power Point Tracking)
- Battery operation: Integrated low voltage disconnect

max. 0,70 kW Input voltage max. 150 V Optimum Vmp** > 68 V Motor current max. 13 A Efficiency max. 98 % -40...50 °C Ambient temp. Enclosure class IP68

Motor ECDRIVE 600-C

- Maintenance-free brushless DC motor
- Premium materials, stainless steel: AISI 304/316
- · No electronics in the motor

Rated power 0,70 kW Efficiency max. 92 % Motor speed 900...3.300 rpm Insulation class F IP68 Enclosure class Submersion max. 150 m

Pump End PE C-SJ3-9

- Non-return valve
- Premium materials, stainless steel: AISI 304
- Centrifugal pump

Efficiency max. 53 %



Pump Unit PU600 C-SJ3-9 (Motor, Pump End)

Borehole diameter min. 4,0 in Water temperature max. 50 °C

Standards



2006/42/EC, 2004/108/EC, 2006/95/EC

IEC/EN 61702:1995, IEC/EN 62253 Ed.1

The logos shown reflect the approvals that have been granted for this product family. Products are ordered and supplied with the approvals specific to the market

**Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature







20

- 10

0

0,8

PS2-600 C-SJ3-9

Solar Submersible Pump System for 4" wells

Pump Chart Vmp* > 68 V80 20 4 25 - 70 30 3,5 60 35 3-40 Efficiency [%] - 50 Output [m³/h] 45 2,5 50 m 40 2 30 1,5

Dimensions and Weights


0,05


1

0,5

0

0





0,15

0,2

0,25

0,3

0,35

0,4

Power [kW]

0,45

0,5

0,55


0,6

0,65

0,7

0,75

A = 545 mm B = 185 mm C = 360 mm D = 96 mm E = 98 mm S = 1,25 in



	Net weight
Controller	5,6 kg
Pump Unit	12 kg
Motor	7,0 kg
Pump End	4,5 kg

^{*}Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature

BERNT LORENTZ GmbH

Siebenstuecken 24, 24558 Henstedt-Ulzburg, Germany, Tel +49 (0)4193 8806-700, www.lorentz.de



